

PRIMARY CHANNEL C-BRACKET



DESCRIPTION

USG C-Brackets are steel accessories used to fasten the Primary Channel into the threaded rod (M6) suspension hanger that is anchored in the ceiling soffit above.

DIMENSIONS

Dimensions: 28 x 40 x 28 x 25 mm

Thickness: 0.50 mm

RAW MATERIALS

- Galvanized steel G40-G90, Yield stress, Fy 33 ksi Ultimate

ASTM & CODE STANDARDS

- Primary Channel C-Brackets are produced to meet or exceed ASTM C635, C645 and C977
- Galvanized sheet steel meets or exceeds requirements of ASTM A-653

GREEN BENEFITS AND RECYCLED CONTENT

LEED Credit MR 2 – USG products are manufactured from cold-formed steel. Steel is 100% recyclable, which helps divert debris from the waste stream.

LEED Credit MR 4 – USG's steel products have a minimum of 25.5% post-consumer recycled content, and 6.8% pre-consumer.

REFERENCES

For further health and safety instructions, refer to the Safety Data Sheet (SDS) for this product, available from your USG Middle East sales office or [USGme.com](https://www.usgme.com)

Notice:

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to [usgme.com](https://www.usgme.com) for the updated products information document.

©2022 Factory of USG Middle East LTD. Co. All rights reserved.