

SHEETROCK HAND TOOL



FEATURES & BENEFITS

- Easy to Handle and Balance: Redesign grip weight and length to be more easier to handle and balance
- Comfortable Soft Grip: Provide high strength as grip materials makes tools holding soft and comfortable
- Stainless Steel Blade: 3CR13 materials for Joint Knife to make the blade rigid and flexible. 301 stainless steel material for Taping Knife to be high anti-corrosion
- Pull Testing to Ensure Strong and Lasting Connection: Pass 50 kg of handle pull testing with two pins to lock blade to grip as premium image
- Steel Cap with Lead Content: Mark damage gypsum board for repair, tap screw head into the gypsum board while improper screw fixing

INTENDED FOR

- For all types of walls and ceiling finishing
- For interior and exterior finishing application
- Up to 50 kg of handle pull testing

PRODUCT RANGE

100mm Joint Knife

- Used for taping compound into the joint or corner
- Used for patching holes when repairing plasterboard damage

150mm Joint Knife

- Used for taping compound into the joint or corner
- Apply compound for the first coat of joint

200mm Taping Knife

- Used for plastering 2nd coat compound into the joint or corner

250mm Taping Knife

- Used for plastering 3rd coat compound into the joint or corner

300mm Taping Knife

- Used for the skimming of compounds on walls or ceilings

Notice:

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to usgme.com for the updated products information document.