

# USG MIDDLE EAST FIRE RATED ACCESS PANEL



## INTENDED FOR

### FEATURES & BENEFITS

- Metal Door Leaf and Aluminium
- Frame and GKF plasterboard strips for fire
- Self-locking fire bulkhead of GKF and intumescent
- Flush-integrated metal door with recessed square lock
- Medium acoustic performance
- Simple wall installation through mounting claws

## APPLICATION

- For wall installation
- For installation fire bulkhead can be removable
- For installation in shaft walls, plumbing walls, brick wall and gypsum blocks
- Tested of fire resistance class 90 minutes and 120 minutes according to EN 1364-1 and EN 1634-1
- Certified by EN 13501-2
- Up-to 31dB Acoustic performance of sound attenuation

## MATERIALS

Length X Width (Nominal)	Length X Width (Service)	EI90/EI 120
200 x 200	200 x 200	•
400 x 400	300 x 300	•
500 x 500	400 x 400	•
600 x 600	500 x 500	•
600 x 1200	500 x 1100	•

Description	Material	Specification
Plasterboard	Fire rated plasterboard	25 mm
Intumescent	Roku-Strip	Z-19.11-1190
Lock	Steel	
Metal frame	Aluminum	ALMgSi0, 5F22
Door leaf	Galvanized Steel	
Steel clamps	Steel	
Handle	Steel / Plastic	
Hinge	Steel	
Drywall screws	Steel	

## MAINTENANCE

- Visual Inspection
- Function
- Cleanness
- Completeness
- Damage
- Condition of the seal

### Notice:

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to [usgme.com](http://usgme.com) for the updated products information document.