

USG MIDDLE EAST MOISTURE AND MOLD RESISTANT ACCESS PANEL



INTENDED FOR

FEATURES & BENEFITS

- Aluminium Frame
- Resistant to moisture, mold and mildew plasterboard panel
- All-round lip seal
- Safety catch on both sides
- Hidden snap

APPLICATION

- For wall and ceiling installation (not to be exposed to walking/traffic loads)
- Suitable for use in moist rooms
- If installed in walls the lock is aligned to the ceiling

Length X Width (Nominal)	Length X Width (Service)	1 x 12.5 mm	1 x 15 mm	2 x 12.5 mm
300 x 300	257 x 291	•	•	•
300 x 600	257 x 591	•		
500 x 500	457 x 491	•		
600 x 600	557 x 591	•	•	•
600 x 1200	557 x 1191	•		
800 x 800	757 x 791	•		
1000 x 1000	957 x 991	•		

MATERIALS

Description	Material	Specification
Frame components	Extruded sections, anodizing quality	Al Mg Si 0.5 F22
Fixing brackets Snap holder Corner connector	Slit strip steel, sheet steel, fully galvanized	DC01 AM 1.5 mm
Limiting plate		
Spacer	Slit strip steel, sheet steel	DX51D/Z275 1.0 mm
Plasterboard	Resistant to moisture, mold and mildew	
Catch arm	Plastic	PP20
Lock	Steel / plastic	
Seal	Lip seal	EPDM
Drywall screws	Steel	

MAINTENANCE

- Visual Inspection
- Function
- Cleanness
- Completeness
- Damage

Notice:

As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to usgme.com for the updated products information document.